

Industry-fastest, laser fax machine with duplex ADF is ideal for robust, everyday use

i-SENSYS
FAX-L410

you can



Robust, fast Super G3 laser fax machine, with large memory and duplex ADF.

This robust, compact Super G3 laser fax machine, with its large LCD display, fast performance and automatic duplex ADF, is ideal for everyday use within any business.

Key features

- Industry-fastest Super G3 fax modem (33.6kbps) – 3 seconds per page* transmission
- Robust, space-saving design with large LCD display
- Ultra High Quality 256 grayscale imaging for clearer detail on faxes
- Large 512-page* transmit and receive fax memory
- 39 one-touch and 200 coded speed dials
- 50-sheet Duplex ADF for automatic double-sided copying and faxing
- Fast laser print and copy speed of 25ppm
- No waiting with Quick First-Print from sleep mode
- High energy efficiency
- Handset as standard

* Based on ITU-T Standard Chart No. 1

What's in the box

Main unit, handset, handset cradle, handset clamp, cartridge 728 starter, power cord, telephone line cable, destination labels, starter guide and warranty card – with user software and manual CDs.

Dimensions (W x D x H)

472mm x 445mm x 358mm

Supported OS

Windows 7 / XP / Vista

Mac OS Version 10.4.9 and up
(Web distribution only)

Linux (Web distribution only)



PRINT



COPY



FAX



SCAN

Canon



Specifications:

FAX UNIT TYPE Type Compatibility Applicable line Modem speed Print technology Scanner type	Standalone facsimile & Laser printer Group 3 PSTN 33.6kbps (Super G3) Laser beam printing Duplex Sheet fed
FAX SCANNING FEATURES Automatic document feeder Document size Effective scanning width Scanning speed Fax resolution Image processing system Halftone	50 sheets (ADF) Width - 216mm (Max), 140mm (Min) Length - 356mm (Max), 127mm (Min) 214mm Approx. 2.5 sec / page Approx. 20 pages / minute Up to 200 x 400 dpi UHQ (Ultra High Quality) 256 shades of grayscale
FAX PRINTING FEATURES Printing method Print speed First Print Out Time Print resolution Print Quality Paper capacity Print cartridge Print cartridge yield Page collated print (on reception) Paper output tray capacity Media Types Media Sizes Printing width Toner save mode Auto image reduction on reception	Laser Beam Printing 25 pages per minutes 5.8 secs 600 x 600 dpi Up to 1200 x 600 dpi 250 sheets CRG728 All in One cartridge Approx. 2100 pages ^{1,2} Yes 100 sheets Plain paper, Heavy paper, Recycled paper, Transparency, Label, Envelope Cassette: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard, Envelope: COM10, Monarch, C5, DL Min. 76.2 x 148mm to Max. 216 x 356mm ADF: A4, B5, A5, B6, LTR, LGL, STMT Min. 127 x 140mm to Max. 356 x 216mm 206mm Yes Yes (75 to 100% in 1% increments)
TRANSMISSION AND RECEPTION FEATURES Transmission speed Compression method Memory transmission Fax memory Memory backup Memory reception Dual access Error correction mode(ECM) Delayed transmission Sequential broadcast Reception Sub-address transmission Error re-transmission Fax transfer	3 seconds per page with 33.6kbps modem ³ MH, MR, MMR Yes 512 pages ³ Unlimited Yes Yes Yes Yes Yes (250 locations) Max. 249 destinations Yes Yes Yes Yes
SECURITY AND MANAGEMENT FEATURES Password user restriction Forced memory reception System management password Reports Transmission header Reception footer	Yes Yes Yes Activity Management Report (TX/RX), Activity Result Report Yes Yes

TELEPHONY FEATURES One-touch dials Coded dials Group dials Program dial Redial Dial search FAX/TEL auto switch Answering machine Hook-up Remote reception On Hook key Telephone handset Type	39 200 Max. 238 dials / Max. 238 destinations Yes Yes (automatic and manual) Yes Yes Yes Yes Yes Yes Standard
COPIER FEATURES Copy resolution Copy speed (Mono) Multiple copy Zoom First copy output time (FCOT)	TEXT/PHOTO mode, TEXT mode, PHOTO mode: 600 dpi x 600 dpi 25 pages per minutes Up to 99 copies 25% - 400% in 1% increments Less than 9.0 seconds
DISPLAY Type Size Languages Energy saver key	LCD 5 lines 23 languages: (English / Spanish / French / Italian / Hungarian / Dutch / Norwegian / Polish / Greek / Estonian / Croatian / Bulgarian / Portuguese / Slovene / Slovak / Finnish / Swedish / Turkish / Russian / Czech / Danish / German / Romanian) Yes
PRINTER FEATURES Interface PDL Memory Printer Supplied Drivers	USB 2.0 Hi-Speed UFR II-LT 128MB Windows 7 / XP / Vista / Mac OS X 10.4.9 and up ⁴ / Linux ⁴ Printer Driver, Fax Driver, Address Book Tool
GENERAL FEATURES Duty Cycle Warm-Up time Recovery time Dimensions (W x D x H) Installation space (with trays handset) Weight Power consumption Acoustic Noise Levels Operating Environment Power Source	Max 10,000 pages per month Approx. 13.5 seconds or less from power on Approx. 2.0 seconds 472 x 445 x 358mm 472 x 704 x 606mm Approx. 13.9kg Maximum: 1320W, Active: 560W, Standby: 4.5W Sleep: 1.4W, Typical Electricity Consumption (TEC): 0.6kWh/w Sound Power: Active: 6.5B, Standby: 4.3B or less Sound Pressure: Active: 50dB, Standby: Inaudible Temperature: 50 to 86°F (10 to 30°C) Humidity: 20% to 80% RH (no condensation) 220 - 240V (±10%), 50/60Hz (±2Hz)
Standard disclaimers. All specifications subject to change without notice 1] Based on ISO/IEC 19752 2] Ships with 1000 pages starter cartridge 3] Based on ITU-T Standard Chart No. 1 4] Web distribution only	



Canon Electronics Inc
canon.com

Canon Europe
canon-europe.com

European Edition 0000
© Canon Europa N.V.,
2012 (0000)