

# PRODUCT DATASHEET ENDURA Classic Cascade Wall E27 Clear

ENDURA® CLASSIC CASCADE | Contemporary aluminium luminaires with amber or clear colored glass diffusor



## Areas of application

- Building facades
- Patios, balconies
- Pathway lighting
- Driveways

# Product benefits

- High flexibility in the choice of the light source thanks to E27 socket
- Easy and quick installation

#### **Product features**

- Direct illumination
- Light cover material: glass
- Light cover appearance: amber or clear
- Housing material: aluminum
- Housing color: RAL 7016
- Type of protection: IP44



## **TECHNICAL DATA**

# Electrical data


Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	1
Operating mode	Mains voltage

## Photometrical data

Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG0

# Dimensions & Weight

Length	160.00 mm
Width	120.00 mm
Height	180.00 mm
Product weight	1055.00 g



# Materials & Colors

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum
Cover material	Glass
Mercury content	0.0 mg

# **Application & Mounting**

Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44

Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Wall
Application environment	Outdoor
With light source	No
Holder designation	E27

# **Emergency lighting**

Type of emergency light operation	Non-maintained
Luminous flux in maintained operation mode	-
Luminous flux in emergency operation mode	-

# Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No

# Additional product data

Product remark	Maximum bulb wattage: 25 W
Number of illuminants	1

# **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	PDF User Instruction ENDURA CLASSIC CASCADE	
PDF	Legal information	Legal insert I-Outdoor
PDF	Declarations of conformity	EC_ENDURA CLASSIC PIPE_ENDURA CLASSIC CASCADE
PDF	Declarations Of Conformity UKCA	Fixed LUM without EMC

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075554337	Folding box 1	125 mm x 165 mm x 210 mm	1159.00 g	4.33 dm <sup>3</sup>
4058075554344	Shipping box 4	350 mm x 270 mm x 230 mm	5140.00 g	21.74 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.