

Cadu 1500

Intelligent power provider

PN: UPCMTLS615HCAAZ01B

EAN: 6422956009717



Specifications

Capacity	1500 VA / 900 W
Type	Line-Interactive
Input	
Nominal Voltage	230 VAC
Accepted Voltage Range	176 – 280 VAC
Frequency Range	50Hz / 60Hz (Auto Sensing)
Input surge protection	475 Joules
Output	
Nominal Voltage	230 VAC
Accepted Voltage range	230 VAC, +/- 10% (3% tolerance accepted)
Frequency Range (Batt. Mode)	50 Hz / 60Hz ± 1%
Power Factor	0.6 @ nominal voltage (100% load)
Waveform (Batt. Mode)	Simulated Sinewave
Transfer Time	2-6 ms typical
Indicators type	
LCD	Standby mode, AC mode Overload mode, Battery mode Self-Test mode Battery replacement mode Fault Mode
Alarm	Battery mode, Overload mode, Battery replacement, Fault mode
Protection	
Outlets type	4 x Schuko Battery Backup RJ11/RJ45 Phone and network protection with 1Gb/s
Full protection	Over/Under voltage protection, discharge and overcharge protection, surge protection
Environement	
Protection class	IP20
Noise level	Less than 45dB
Humidity	0-90 % (non-condensing)
Temperature	0-40°C



HID USB
port



1Gb/s LAN
protection



Extended
back-up
time


- 1Gb/s LAN surge protection
- HID USB communication port
- Auto-Restart while AC is recovering
- Battery Replacement Alarm
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Off-Mode Charging
- Cold start function
- LCD light dimming at 20%

Battery

Battery Type & Number	2 x GP09122F
Typical Recharge Time	3 hours (4 hours for fully depleted batteries)
Running time on battery (minutes)	25% Load - 27 min 50% Load - 6 min 75% Load - 3min 100% load - 1 min
Management	
Communication port	HID USB
Software	https://www.power-software-download.com/viewpower.html
Physical	
Product dimensions	390 x 146 x 205 mm
Product weight	11.1 kg
Retail pack dimensions	490 x 230 x 287 mm
Retail pack Weight	12.1 kg



Running time on battery



Logistics

Carton Box Size (LxWxH)	495 x 235 x 297 mm
Pieces in the Carton Box	1
Net & Gross weight / CTN	NW: 11.1 kg / GW: 12.1 kg



Certificates

RoHS 
2011/65/EU

* for a decent backup time we recommend to load the ups up to 75% of its maximum capacity

