

## 4x2P+E (Schuko) extension sockets, USB A + C charger, Quick charge, 1.4m H05VV-F 3x1mm<sup>2</sup>, gray

ORNO

Marka: Orno | Symbol: OR-AE-13247(GS)/G | Ean: 5908254825767



### PRODUCT DESCRIPTION

4x2P+E (Schuko) extension sockets, USB A + C charger, Quick charge, 1.4m H05VV-F 3x1mm<sup>2</sup>, gray

## TECHNICAL DATA

### General information:

|                                                            |                     |
|------------------------------------------------------------|---------------------|
| Housing shape:                                             | Square              |
| Wire cross-section:                                        | 1,5 mm <sup>2</sup> |
| Number of socket outlets with protective contact (SCHUKO): | 4                   |
| Length of power cord:                                      | 1.4 m               |
| Nominal current:                                           | 16 A                |
| USB charger:                                               | Yes                 |
| Output current of the USB charger:                         | 3.1 A               |
| Frequency:                                                 | 50 Hz               |
| Safety shutters:                                           | Yes                 |
| Dimensions - width:                                        | 77 mm               |
| Dimensions - height:                                       | 77 mm               |
| Dimensions - depth:                                        | 77 mm               |
| Number of USB connections:                                 | 2                   |
| Colour:                                                    | Grey                |
| Material:                                                  | Plastic             |
| Degree of protection (IP):                                 | IP20                |
| Surface finishing:                                         | Matt                |
| Output voltage of the USB charger:                         | 5 V                 |
| Output power of the USB charger:                           | 15.5 W              |
| USB port type:                                             | USB-A + USB-C       |
| Quickcharge:                                               | Yes                 |
| Quickcharge Type:                                          | 3.0                 |
| Minimal output voltage of Quickcharge:                     | 5 V                 |
| Minimal output current of Quickcharge:                     | 3 A                 |
| Minimal output power of Quickcharge:                       | 15.5 W              |

|                                        |               |
|----------------------------------------|---------------|
| Maximum output voltage of Quickcharge: | 12 V          |
| Maximum output current of Quickcharge: | 1.67 A        |
| Maximum output power of Quickcharge:   | 20 W          |
| Operating temperature:                 | -5 - +35°C    |
| Nominal voltage:                       | 230 V         |
| Max. load:                             | 3680 W        |
| Number of wires:                       | 3             |
| Insulation type:                       | PVC           |
| Material quality:                      | Thermoplastic |
| Weight:                                | 0.54 kg       |



