

CERTIFICATE OF CONFORMITY

Electromagnetic Compatibility (EMC) Directive 2014/30/EU

This Certificate of Conformity is hereby issued to the product designated below:

Certificate No...... 24EP08247E01

Report No..... EP2408247E01

Date Issue..... 2024-09-19

Applicant's name HANGZHOU HIKSTORAGE TECHNOLOGY CO., LTD.

Address...... Room 307, Unit B, Building 2, 399 Danfeng Road, Binjiang District,

Hangzhou, Zhejiang

Manufacturer's name......: HANGZHOU HIKSTORAGE TECHNOLOGY CO., LTD.

Hangzhou, Zhejiang

Product Description 67W USB 2C Fast Wall Charger

Model(s)/Type References: HS-HUB-GaN67, HS-HUB-GaN67 EU, HS-HUB-GaN67 SEMI,

HS-HUB-GaN67 SEMI EU

Output: See attachment for details

Standard(s)..... EN 55032:2015+A11:2020+A1:2020

EN 55035:2017+A11:2020

EN IEC 61000-3-2:2019+A1:2021

EN 61000-3-3:2013+A1:2019+A2:2021

On the basis of the referenced test report(s), sample(s) tested of the above product have been found to comply with the standards harmonized with the directives listed on this verification at the time the tests were carried out. Other standards and Directives may be relevant to the product. This verification is part of the full test report(s) and should be read in conjunction with it(them).

Once compliance with all product relevant CE mark directives are verified, including any relevant e.g. risk assessment and production control, the manufacturer may indicate compliance by signing a Declaration of Conformity themselves and applying the mark to products identical to the tested sample(s).

Approved By

Eric Liu

Director of engineering department



CERTIFICATE OF CONFORMITY

Electromagnetic Compatibility (EMC) Directive 2014/30/EU

Appendix of Certificate No.: 24EP08247E01

Model list:

Model	Output
HS-HUB-GaN67, HS-HUB-GaN67 EU, HS-HUB-GaN67 SEMI, HS-HUB-GaN67 SEMI EU	USB-C1: 5.0V=3.0A, 9.0V=3.0A, 12.0V=3.0A, 15.0V=3.0A, 20.0V=3.25A, 20.3V=3.3A 67.0W Max USB- C2: 5.0V=3.0A, 9.0V=3.0A, 12.0V=3.0A, 15.0V=3.0A, 20.0V=3.25A, 20.3V=3.3A 67.0W Max USB-C1+C2: 5.0V=3.0A, 9.0V=3.0A, 12.0V=3.0A, 15.0V=3.0A, 20.0V=2.25A 45W max+5.0V=3.0A, 9.0V=2.22A, 12.0V=1.67A 20W max